

SF6 Areacheck P2

DETECTION PRINCIPLE

- SF6: NIC

RANGE

- 0 - 2000 ppm SF6

RESOLUTION

- 500 ppm SF6 /10 ppm

MAINS POWER

- 100 - 240 VAC, 50/60 Hz

POWER CONSUMPTION

- 18VA

OPERATING TEMPERATURE

- -5°C to 45°C

STORAGE TEMPERATURE

- -20°C to 60°C

OPERATING HUMIDITY RANGE

- 10 - 90% non condensing

MAX LOAD, RELAY OUTPUT

- 2.5A / 230 VAC

SIZE

- H 280 x B 165 x T 125 mm

PROTECTION CLASS

- IP 52

NOISE LEVEL OF AUDIBLE ALARM

- > 75 dbA, 1m

WEIGHT

- 1,5 Kg (w/o wall mounting bracket)

FUSE

- T 1A (Slow Blow)



SF6 AreaCheck P2	Description	Price
ACP2	SF6 Areacheck P2	\$3,470.00

SF6 AreaCheck P2 Access	Description	Price
P2-100-0006	AreaCheck Replacement Sensor	\$1,850.00
P2 Program Cable	AreaCheck P2 Programming Cable	\$160.00

SF6 AreaCheck P2 Repair	Description	Price
P2AC Exchange Sensor	Area Check Exchange Sensor	\$760.00